

Pillar Slim TouchPoint

AC 2 × 22 kW

An intelligent AC charging station with two charging points and up to 22 kW per point. Charge while vehicles are parked at home, at work or at your premises. A freestanding station for two parking spaces, suitable for indoor and outdoor installation.



Cable version



Socket version on SolidBase

Choose the version

Two Type 2 sockets: drivers use their own cable. With the supported setting, a cable can remain locked at the station and be replaced after unlocking.

Two fixed cables: ready to connect a vehicle. The standard length in this sheet is 5 m. Other versions are confirmed in the quotation.

Installation and customization

SmartBase for installation in the ground or SolidBase for solid surfaces. Anchoring and installation are ordered separately. Selection depends on the surface and cable route.

The owner may choose their own station branding. Options and scope are agreed for the site.

Documents, current versions and quotations

View this product at agevolt.com

Technical specifications

Number of charging points (EVSE)	2
Maximum power per point	22 kW
Socket version	Type 2 Mennekes (IEC 62196-2)
Cable version	Type 2 Mennekes (IEC 62196-2), 5 m
Rated voltage	3 × 400/230 V AC, 24 V DC
Rated current	63 A
Rated frequency	50 Hz
Protection level	IP54
Mechanical impact resistance	IK10
Overall dimensions (W × H × D)	195 × 1 500 × 250 mm
Weight	15 kg
Operating temperature	-30 °C to +50 °C
Operating humidity	5 % to 95 %
Storage temperature	-30 °C to +60 °C
Access for installation	Rear door
Electricity meter	MID Class 1
Protection	RCD DC 6 mA, RCBO AC, type A, 30 mA
Configuration	TouchPoint
Surge protection (optional)	B+C+D
Platform communication protocol	OCPP 1.6-J
NFC tags on the station	2
Status indication	2 LED columns

TouchPoint

5.5" multi-touch display, 720 × 1280 • RFID/NFC: ISO 14443 A/B and Mifare
4G / 3G / 2G • Dual-band Wi-Fi • Bluetooth 5.0 • 100 Mbps Ethernet

MyAgeVolt and charging power

TouchPoint handles station operation and communication. It replaces the original display and internal SmartSystem. OCPP 1.6-J connects the station to standard charging platforms. MyAgeVolt provides remote management, reporting, sharing according to the owner's prices and rules, and fleet management. Actual power depends on configuration, each vehicle's AC charger, the available supply and energy management. AC vehicle charging is typically 3.7 to 7.4 kW for single-phase cars and 11 to 22 kW for three-phase cars, limited by the station version.